

WRIGHTWAY2MT® INDUSTRIAL BIN TIPPER / BIN LIFTER

p: 02 6622 7111 f: 02 6622 7131

www.wrightway.com.au

No pinch points: All access areas have been made safe ALL OPERATIONAL MOVING PARTS TRAVEL WITHIN COVERED and SHIELDED PANELS

FULLY CAGED:

• 9mm diamond galvanised + powder coated finger proof guarding

Solid foot guarding at base.

ADVANCED ELECTRONICS:

• Category 3 integrated interlock safety system (mechanism fully protected);

• Electronic sensors ensure doors CANNOT BE OPENED unless cradle is on the ground;

- Battery charger indicator LED;
- Control Box access by Authorised Technicians only;

• Electronic and Manual over-ride to open doors (Auth Techs only);

• Crane lifting points.





MACHINE WILL NOT OPERATE UNLESS:

- both doors are closed,
- the cradle is at ground level,
- & electronic sensors are aligned.

NO CHUTE:

Therefore no cross contamination between different sized bins

STANDARD MACHINE FEATURES:

- Lift and empty up to 450kg;
- Regulated lowering by gravity: pressure relief valve prevents over-loading;
- Dedicated fork-lift pockets: safe relocation;
- 12 month warranty (machine & battery);
- Spare parts and diagnostic assistance from manufacturer beyond Warranty.

OPERATOR SAFETY:

• Operator, Control Panel and Safe Operating Procedure located at the front of machine, away from skip;

• Emergency Stop button;

• Handle bars at either side of machine for safe relocation by 2 operators;

• Doors open wide: safe access for loading and unloading of cradle;

•Braked castors at front, winddown brake levers at rear to ensure stability during lift/empty;

• Cradle suits 660 and 1100 litre 4-wheeled bins + standard wheelie bins: no manual adjustment necessary;

• Detailed Operator Manual.



on-site staff training + excellent after sales service email:Sales@wrightway.com.au